

Fiber Optic Video & Data Transmission 8-Channel Video + 1 Duplex Data + IP Ethernet

8 →
Video

System Design

Fiber Optic Video & Data Transmitter & Receiver
ZW-80101FDET/R can transmission 8-Channel digital composite video, 1 duplex data, and 10M/100M Ethernet, Data support RS485, RS232, RS422 protocols. Ideal for Broadcast /Studio ,CCTV and Professional AV applications.



Audio

Stand-alone or rack-mount. All units of VOS-80101FDET/R come in an insert card version. The cards can be inserted into our 14-slot,19inch 4U or 6U rack-mountable card cage (ZW-CH04 or ZW-CH06). One 8-Channel video card require two slots widths.

↔ **1** ↔
Data

Single-Mode or Multi-Mode, ZW-80101FDET/R can support FC/PC or ST/PC Optical connector, can be used in Daisy-Chain system (Need to customize). The Transmission distance range according to the Optical Budget. Manufacturer's standard is: Single-mode 20km or Multi-mode 1.2km.


↔ **1** ↔
Ethernet



Features

- Support Point-to-Point or Daisy-Chain connection
- Uncompressed Digital Composite Video over one fiber
- Data support RS485(2-wire or 4-wire),RS232,RS422, Contact Closure
- Compatible with all PAL, NTSC,SECAM Video Systems
- Multi-mode Fiber Support for Distances up to 1.2 km
- Single-Mode Fiber Support for Distances up to 100 km
- LED Status Provide Rapid Indication of Operating Parameters
- No EMI or RFI and no ground loops
- Stand alone or rack-mount

Typical Configuration



Video & Data over Fiber

Ordering Information

Model Number		Fiber Mode	Wavelengths	Optical Power Budget	Maximum Transmission Distance
Transmitter	Receiver				
ZW-80101FDEMT	ZW-80101FDEMR	Multi-Mode	1310nm/1550nm	10dB	1.2km
ZW-80101FDEST	ZW-80101FDESR	Single-Mode	1310nm/1550nm	12dB	20km
ZW-80101FDEST-4	ZW-80101FDESR-4	Single-Mode	1310nm/1550nm	18dB	40km
ZW-80101FDEST-6	ZW-80101FDESR-6	Single-Mode	1310nm/1550nm	25dB	60km

Note:

- The Optical Power Budget data fit Multi-mode(62.5/125 μ m), Single-Mode(9/125 μ m).
- When using 50/125 μ m multimode fiber, subtract 3 dB from the optical power budget.
- Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.
- Maximum transmission distance is also limited by fiber bandwidth.
- Power adapter is manufactured by third party and is supplied with fitted screw-terminal output cables. Power adapter included (for standalone) US, European, UK or Australian power plug.
- Please feel free to consult factory for any special requirement and customization

Specification

<ul style="list-style-type: none"> • Video 	<ul style="list-style-type: none"> • Connectors
<ul style="list-style-type: none"> Number of Channels: 8-Channel Video Input/output impedance: BNC 75Ω Input/output Compatibility: PAL, NTSC, SECAM Input/output voltage: 1.0 Volt p-p Bandwidth: 6.5MHz Bit Resolution: 8-Bit Digital Transmission Differential Gain: < 1.5% Differential Phase: < 1.5° Tilt: < 5% Signal-to-Noise Ratio(SNR): > 67 dB 	<ul style="list-style-type: none"> Video: 75Ω BNC (Gold Center Pin) Data: Terminal Block Optical: FC/PC or ST/PC Optional Stand-Alone Power: Screw terminal block Rack Power: AC line cord
<ul style="list-style-type: none"> • Data 	<ul style="list-style-type: none"> • Electrical & Mechanical
<ul style="list-style-type: none"> Data Formats: RS485(2-wire or 4-wire), RS232/422, Contact Closure Data Rate: DC to 115.2Kbps Bit Error Rate: 10E-9 	<ul style="list-style-type: none"> Input Power Requirements: DC 5V@3A Power Adapter: AC 100V~240V Power Consumption: < 5W Stand-Alone Dimensions: 176.5mm \times 158mm \times 59mm Card for 4U Rack Dimensions: 145mm \times 170mm \times 45.4mm Shipping Weight: 2.5kg (include TX & RX)
<ul style="list-style-type: none"> • Ethernet/IP 	<ul style="list-style-type: none"> • Environmental
<ul style="list-style-type: none"> Standard: Ethernet IEEE 802.3 Data Rate: 10/100 Mbps Connector: RJ-45, Auto MDI/MDI-X 	<ul style="list-style-type: none"> Operating Temperature: -45° C ~ +75° C Storage Temperature: -45° C ~ +85° C Relative Humidity: 0% ~ 95% (non-condensing) MTBF: > 100,000 hours